

# AquaRite® LT SV

An affordable, high quality salt chlorinator with transparent cell

- **New options available** for this easy-to-use salt chlorinator
- **Optional ORP kit** regulates the chlorine production
- **Automatic pH correction kit** available as an optional extra
- **Simple** to install, simple to use
- **Closed pool cover detection** for an instant reduction in chlorine production
- **Salinity detector**
- **Transparent cell** to enable a visual check of the production.  
Gas sensor included.



Optional ORP kit  
Standard probe



pH correction kit (optional)

AQUARITE LT

Description	AQR-LTO-SV16	AQR-LTO-SV22	AQR-LTO-SV33	AQR-LTO-SV50
Maximum production Cl <sub>2</sub> /h	16 gr	22 gr	33 gr	50 gr
Salt concentration	From 3gr up to 100 gr Na/Cl			
Pool volume	65	110	200	300
Display	2,8" TFT			
Alimentation	220 V 50/60 Hz			
Dimensions	270 x 220 x 115 mm			
Electronic box	Fireproof black ABS plastic			
Front cover	Black ABS plastic			
Output	8-15 A	8-20 A	10-15 A	35-45 A
Consumption	120 W	160 W	150 W	360 W
pH control	Yes			
ORP control	Optional			
Temperature control	Yes			
Automatic cleaning	Operates by reverse polarity			
Salinity testing	Salinity detected in g/l (accuracy +- 10%)			
Pool cover	Programmable 0 – 100% production as a function of pool cover being open or closed			

**NEW**

## AQUARITE LT TRANSPARENT CELL

AVAILABLE  
OPTIONS

Description	AQR-PLUS-SV16ST	AQR-PLUS-SV22ST	AQR-PLUS-SV33ST	AQR-PLUS-SV50ST
PH standard probe kit	AQR-LT-KITPH2	AQR-LT-KITPH2	AQR-LT-KITPH2	AQR-LT-KITPH2
ORP standard probe kit	AQR-LT-KITORP	AQR-LT-KITORP	AQR-LT-KITORP	AQR-LT-KITORP

**NEW**

## AQUARITE LT TRANSPARENT CELL

AVAILABLE  
OPTIONS

Description	AQR-PLUS-SV16ST	AQR-PLUS-SV22ST	AQR-PLUS-SV33ST	AQR-PLUS-SV50ST
Electrolysis cell	4 Titanium cell plates MONOPOLAR	5 Titanium cell plates MONOPOLAR	7 Titanium cell plates MONOPOLAR	5 titanium plates MONOPOLAR
Minimum flow	5 m <sup>3</sup> /h	7 m <sup>3</sup> /h	9 m <sup>3</sup> /h	9 m <sup>3</sup> /h
Dimension cell plates	200 x 45 mm	200 x 45 mm	200 x 45 mm	400 x 45 mm
Material cell housing	Plastic PVC transparent			
Cell fastener	Thread for an easy installation			
Diameter tube connection	63 mm			
Dimension cell	355 x 305 x 305 mm			
Cell cable size	(3 x 4) x 1.5 m			
Gas sensor	Included in the cell			Flow switch
Maximum pressure	4 Kg/cm <sup>2</sup>			
Maximum temperature	45°C			