

# AquaRite® Flo



YEARS OF WARRANTY

**3** STANDARD 8000 HOURS



## A SALT CHLORINATOR EASY TO USE

- **Salt chlorinator** covering a wide range of chlorine production: 8, 16, 22, 33 and 50 g/h/cl
- Production configuration thanks to the **LED display**
- **Transparent cell** for visual checks on production
- Detection of presence of a pool cover for adjustment of chlorine production
- **Flow detector kit** included by default
- **9 levels possible** of chlorine production



**INCLUDED**



Cl Production only

External control

**Complete your installation...**

...with **EASY-CHEM-SPH** and **EASY-CHEM-SRXGS**



**Installation of the cell in piping**  
 > Installation in a vertical position, on by-pass, at the highest point of the installations

AQUARITE® FLO

Description	AQR-FLO-8	AQR-FLO-16	AQR-FLO-22	AQR-FLO-33	AQR-FLO-50
Production in	8 g/h	16 g/h	22 g/h	33 g/h	50 g/h
Chlorine production	9 levels possible				
Pool size up to	30 m³	75 m³	100 m³	150 m³	200 m³
Salt concentration	3 to 100 g/L				
Display	LED light				
Superchlorination mode	•	•	•	•	•
Manual adjustment of Cl (%)	•	•	•	•	•
Gas detector	•	•	•	•	No
Flow Switch	•	•	•	•	•
Cover detection	•	•	•	•	•
Closed pool cover detection	Yes				
External redox control	Dry contact				
Dimensions	400 x 400 x 210 mm				
Weight	9 kg	9 kg	10 kg	10 kg	10 kg
Alarm	Salt level / flow				