

Outlet fittings

YEARS OF WARRANTY

3
STANDARD

SP SERIES

Code	Reference	Colour	Ball Ø mm	Flow (m³/h)	Pool type	Threaded connection	Slip connection
SP1411ELL19D	Multi-directional outlet 60 - 80 µm (1 gasket)	White	19	4	Liner	ext 2"/int 1,5"	–
SP1411E19D	Multi-directional outlet > 80 µm (2 gasket)	White	19	4	Panel	ext 2"/int 1,5"	–
SP1411ELL19E	Multi-directional outlet 60 - 80 µm (1 gasket)	White	25	7	Liner	ext 2"/int 1,5"	–
SP1411E19E	Multi-directional outlet > 80 µm (2 gasket)	White	25	7	Panel	ext 2"/int 1,5"	–
SP1022E19D	Multi-directional outlet	White	19	4	Concrete	ext 2"/int 1,5"	–
SP1022E19E	Multi-directional outlet	White	25	7	Concrete	ext 2"/int 1,5"	–
SP1023E19D	Multi-directional outlet	White	19	4	Fiberglass	ext 2"/int 1,5"	–
SP1023E19E	Multi-directional outlet	White	25	7	Fiberglass	ext 2"/int 1,5"	–
SP1419A	Multi-directional outlet	White	split eyeball	7	–	ext 1,5" MIP	–
SP1419CE	Multi-directional outlet	White	12	3	–	ext 1,5" MIP	–
SP1419DE	Multi-directional outlet	White	19	4,5	–	ext 1,5" MIP	–
SP1419EE	Multi-directional outlet	White	25	7	–	ext 1,5" MIP	–
SP1420E	Multi-directional outlet	White	25 + flexible end	7	–	ext 1,5" MIP	–



SP1411ELL19D
SP1411E19D
SP1411ELL19E
SP1411E19E



SP1022E19D
SP1022E19E



SP1023E19D
SP1023E19E



SP1419A



SP1419CE



SP1419DE



SP1419DE



SP1420E