Powerline by Hayward®

White and RGB PAR56 LED bulbs

NEW GENERATION ENERGY-SAVING LIGHTING



ASSETS - WHITE LED BULB

- Easy to install
- For all types of existing and new pools
- PAR56, 90 LEDs
- 1600 lumens
- 12 V\18W 50Hz / 60Hz



ASSETS - RGB LED BULB


• Easy to install

- Multicolor RGB
- For all types of existing and new pools
- PAR56, 90 LEDs
- 11 fixed colors
- and 5 color sequences
- 800 lumens
- 12 V∿18W 50Hz / 60Hz



		Description	81481	81480			
WHITE LED B	E AND RGB ULBS	Consumption in W	18	W			
		Power supply	12 VCA				
		Number LEDs	9	0			
		Lumens	1600 lumens 800 lumens				
		Scatter angle	12	0°			
		White / RGB	Cool white (6500K)	RGB			
		LED technology	CrystaLogic®	ColorLogic® (16 programs, synchronisation, memory)			
		Plastic part	Assembly kit for installation in all types of niche				
		Radiofrequency	Νο				
		Remote Control	No				
		Energy Efficiency		The EU2019/2015 and EU2019/2020 regulations do not apply to this RGB light.			

Dimensions in mm



₩ Ţ TIPS

Remember to finalize your order with one of our Hayward® products



H-POWER & H-POWER Connect 50, 100

and 300 W transformers available



Radiofrequency controllers

White and RGB flat LED bulbs


REPLACEMENT BULB COMPATIBLE WITH ALL EXISTING PROJECTORS



ASSETS - RGB FLAT LED BULB

- Replacement bulb compatible with all existing projectors (Cofies, Kripsol[®], Astral...)
- Fitting and assembly kit included
- RGB version (16 programs, synchronization and memory of last color)
- Models for after market (no frame): 18W / 25W / 32W

Description	81486	81487	81488	81489	81490	81491		
Consumption in W	18 W	25 W	32 W	18 W	25 W	32 W		
Power supply	12 VCA							
Number LEDs	252	351	441	252	351	441		
Lumens	1600	2250	2850	800	1100	1400		
Scatter angle			12	3				
White / RGB	Cool white (6500K) RGB							
LED technology		CrystaLogic [®]		ColorLogic® (16	ColorLogic® (16 programs, synchronisation, memory)			
Plastic part	Assembly kit for all PAR56 in niches, and all flat lights							
Radiofrequency	Νο							
Remote Control			N	0				
Energy Efficiency					The EU2019/2015 and EU2019/2020 regulationsdo not apply to this RGB light.			
	Power supply Number LEDs Lumens Scatter angle White / RGB LED technology Plastic part Radiofrequency Remote Control	Power supply Number LEDs 252 Lumens 1600 Scatter angle White / RGB LED technology Plastic part Radiofrequency Remote Control	Power supply Very Supply Number LEDs 252 351 1600 Lumens 1600 Scatter angle 2250 White / RGB Cool white (6500K) LED technology CrystaLogic® Plastic part Ass Radiofrequency Ass Remote Control Image: Control	Power supply 12 Number LEDs 252 351 441 Lumens 1600 Scatter angle 2250 Scatter angle 12 White / RGB Cool white (6500K) LED technology CrystaLogic® Plastic part Assembly kit for all PAR56 Radiofrequency N Remote Control N	Power supply 12 VCA Number LEDs 252 351 441 252 Lumens 1600 2250 2850 800 Scatter angle 120° White / RGB Cool white (6500K) ColorLogic® (166 Plastic part Assembly kit for all PAR56 in niches, and all flat lig Radiofrequency No No Energy Assemble Let and the lige of	Power supply 12 UCA Number LEDs 252 351 441 252 351 Lumens 1600 2250 2850 800 1100 Scatter angle 120° 120° 808 1100 White / RGB Cool white (6500K) RGB RGB LED technology CrystaLogic® ColorLogic® (16 programs, synchronist) Plastic part Assembly kit for all PAR56 in niches, and all flat lights Radiofrequency Remote Control No No The EU2019/2015 and EU2019		





Remember to finalize your order with one of our Hayward® products



Powerline by Hayward®



